



599.00 EUR  
incl. 19% VAT, plus [shipping](#)

- STC-24850 fan-controller

**Support:**  [Cables-Connectors](#)

#### 850W DC ATX P4 Power Supply (18-36VDC)

Now you can power every PC in your truck. 850W power and Pentium-4 connector are giving you all possibilities !  
The ATX connector has 24 pins. Along with the power supply there is a 24pol to 20pol ATX adapter included.

|                              |  |
|------------------------------|--|
| Dimensions                   | 150mm[W] x 184mm[L] x 86mm[H] Standard ATX PS/2 size |
| Weight                       | 3.5 kgs  |
| Input Voltage Range          | 18 - 36VDC   |
| Output Power maximum         | 850W   |
| Output Power maximum (rails) | +3.3V : 30A<br>+5.0V : 30A<br>+12.0V : 60A           |
| Remote sensing               | +5V and +3.3V  |
| Over Power Protection        | Load over 130%±10% of max. output power : shutdown   |
| Over Voltage Protection      | +5V, +12V & +3.3V Auto-recovery                      |
| Short Circuit Protection     | Main outputs shutdown and latch off                  |

---

|                             |   |
|-----------------------------|---|
| Over Temperature Protection | OTP Level is set at 110°C   |
| Operating Temperature       | -20°C ~ +70°C   |
| Storage Temperature         | -40°C~+80°C   |
| Cooling                     | Build-in One 80x80x25mm Ball Bearing Fan with max. air flow 42CFM |

**Note :** Minimum power of 60W must be drawn at system startup time !