




79.95 EUR
incl. 19% VAT, plus [shipping](#)



- Applied Solid Capacitor for CPU VRM to ensure a longer lifespan for system
- ECS Durathon Technology ensure the stability, reliability and performance of system.
- Dual Display design for multiple output support
- Integrated Printer (LPT) port / header to expand functionality
- Microsoft Windows 8 Certified
- Intel ® VRD 12 Ready
- Supports DirectX® 11 to enhance graphical performance
- Supports HDMI 1.4a Technology (resolution up to 1920X1200) and HDCP function
- Free Bundle: CyberLink Media Suite

Supports Intel® CNVi

CPU

Onboard Intel® Bay Trail
processors
On-Board CPU Intel ® Bay
Trail J1900 processor
VRD 12.0
Solid Capacitor for CPU
side
Supports Intel®
Hyper-Threading
Technology

GRAPHICS	Supports DirectX® 11
	Supports Full HD 1080P
	Blu-ray / HD-DVD
	Playback
MEMORY	Single-channel DDR3
	Memory architecture
	1 X DDR3 SO-DIMM
	socket
EXPANSION SLOT	Support up to 8 GB
	1 X PCI Express X 1 Gen 2.0slot(s)
	1 X Mini PCI Express X1 slot(s) for Wi-Fi /Bluetooth modules
	2 X Serial ATAIII 3Gb/s
Storage	6-Channel HD audio
	CODEC Realtek ALC662
	Realtek ALC662 6-channel
	High Definition audio
Audio	CODEC
	Meets performance
	requirements for Microsoft
	WLP 3.08 Vista premium
	and mobile PCs
	Six channel DAC supports
	16/20/24-bit PCM format
	for 5.1 channel audio
	solution
	Emulation of 26 sound
	environments to enhance
	gaming experience
LAN	Voice Cancellation and
	Key Shifting in Karaoke
	mode
	Compatible with Direct
USB	Sound 3D™, A3D™,
	I3DL2
	Realtek RTL8111G
	Gigabit Fast Ethernet
REAR PANEL I/O	Controller
	1 X USB3.1 Gen1 port(s) up to 5Gb/s
	6 X USB2.0 port(s) Up to 480 Mb/s (Back Panel 4 port(s), Onboard 2 port(s))
	1 X PS/2 Keyboard & PS/2
	mouse connectors
	1 X Audio port (Line
	Out/Line In/Mic In)
	1 X RJ-45 port
	1 X HDMI port(s)
	1 X D-Sub (VGA) port(s)
	1 X USB3.1 Gen1 port(s)
	4 X USB2.0 port(s)

**CONNECTORS &
HEADERS**

1 X 4-pin CPU_FAN
connector with smart fan
1 X 4-pin SYS_FAN
connector with smart fan
1 X Front Panel
MIC/Speaker out header
1 X Front Panel
switch/LED header
1 X USB 2.0 header
(Support additional 2 USB
ports)
2 X SATA II 3Gb/s
connector(s)
1 X CLR_CMOS header
2 X Serial port header
(COM)
1 X Parallel port header
(LPT)
1 X LVDS connector
(optional)
AMI BIOS with 8 MB SPI
Flash ROM

SYSTEM BIOS

Supports ACPI 5.0 & DMI
Dual Display
Plug and Play, STR (S3) /
STD (S4) , Hardware
monitor, Multi Boot
Multi-Language BIOS
Audio, LAN, can be
disabled in BIOS
Dual-Monitor function

FORM FACTOR

Mini ITX Form Factor
170*170

OS Support

Windows 7 64-bit
Windows 8.1 32-bit
Windows 8.1 64-bit
Windows 10 64-bit
Windows 10 32-bit

Certifications

CE/FCC Certification
ErP/EuP Certification
WHQL Certification
WHCK Certification