



0.00 EUR
incl. 19% VAT, plus [shipping](#)

- Ultra 7 155U !
- TPM2.0 !
- 2 x 2.5GbE !
- Fanless !



- Powered with with Intel® Core™ Ultra 7 155U
- High-Speed Networking: 2 x 2.5GbE for fast and reliable connectivity
- 4K Display: Supports HDMI@ 2.0b (4096 x 2160@60Hz) for high-resolution output
- Flexible Storage: 1 x SATA III, 1 x M.2 E-Key, 1 x B+M Key paired with 1 x Nano SIM Slot
- Comprehensive I/O: 4 x RS485/422/232, 3 x USB 3.2 Gen 2, 4 x USB 2.0, 2 x RJ45
- Versatile Mounting: Supports desktop, wall mount, and DIN rail installation

SYSTEM

MB FORM FACTOR

CPU

CHIPSET

MEMORY

BIOS

WAKE ON LAN

WATCHDOG TIMER

SECURITY

RTC BATTERY

OS SUPPORT

POWER

POWER REQUIREMENT

POWER ON MODE

DISPLAY

GPU

Performance

Onboard Intel® Core™ Ultra 5 Processor 125U (Formerly Meteor Lake, TDP 15W)

Intel® SoC

2 x DDR5 5600MT/s, Dual Channel SO-DIMM, up to 96GB

UEFI

Yes

255 Levels

TPM2.0

Lithium Battery

Windows® 11 (64bit)

Windows® 10 (64bit)

Linux

DC-in 12~36V

90W Adapter: AC90~240V, DC19V/4.7A

AT / ATX (Default) Mode

Intel® Graphics

Type C DP	1 x Type C DP1.4 (Max Resolution: 4096 x 2160@60Hz)
DP	2 x DP1.4 (Max Resolution: 4096 x 2160@60Hz)
HDMI	2 x HDMI 2.0b (Max Resolution: 4096 x 2160@60Hz)
MULTIPLE DISPLAY	Support 3 Displays
AUDIO	
CODEC	Realtek Audio Codec
AMPLIFIER	3W
LAN	
ETHERNET	1 x RJ45 for Intel® I226-V 2.5GbE 1 x RJ45 for Intel® I226-LM 2.5GbE
SYSTEM I/O	
	4 x Antenna Holes 1 x DC-in 1 x HDMI® 2.0b 1 x DP
REAR PANEL I/O	3 x USB 3.2 Gen 2 1 x USB 3.2 Gen 1 Type-C 2 x RJ45 1 x GND Hold 1 x Power Button 1 x Reset Button 1 x Power LED
FRONT PANEL I/O	1 x HDD LED 4 x USB 2.0 4 x RS-232/422/485 2 x Antenna Holes
EXPANSION	
M.2	1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1) Support CNVi 1 x B-Key 3042/3052 (USB 3.2/PCIe 3.0 x2) 1 x M-Key 2242/2280 (PCIe 4.0 x4 / SATA III) Support NVMe
SIM	1 x Nano SIM Card Slot
MECHANICAL	
MOUNTING	Desktop, Wallmount, Din Rail
DIMENSIONS (W x D x H)	185.0 (W) x 142.0 (D) x 61.0 (H) mm (7.28" x 5.6" x 2.4")
NET WEIGHT	3.5 kg
ENVIRONMENT & CERTIFICATION	
OPERATING TEMPERATURE	-20°C ~ 60°C (-4°F ~ 140°F)
STORAGE TEMPERATURE	-40°C ~ 85°C (-40°F ~ 185°F)
OPERATING HUMIDITY	10 ~ 90% Relative Humidity, Non-condensing
CERTIFICATION	CE/FCC Class A LVD